



Distributed by:

Farrington Electrical Supplies Inc.

36-27 College Point Blvd.
Flushing, NY 11354

Tel. 718-353-8686 Fax 718-353-8582

Nikco® Elite SEER 13 series Ductless Split Unit

Model		MSE-09HRN1	MSE-12HRN1	MSE-18HRN1	MSE-24HRN1
Power Supply		115V, 60Hz, 1Ph	115V, 60Hz, 1Ph	208/230V, 60Hz, 1Ph	208/230V, 60Hz, 1Ph
Refrigerant		R410A / 37.7oz	R410A / 47.6 oz	R410A / 72.0 oz	R410A / 86.4 oz
Cooling	Capacity	9000Btu/h	12000Btu/h	18000Btu/h	23000Btu/h
	Rated current	7.6A	10.0A	6.8A	8.8A
Heating	Capacity	10000Btu/h	12500Btu/h	18000Btu/h	23000Btu/h
	Rated current	7.6A	10.0A	7.0A	8.8A
Design Pressure	Hi	550psi	550psi	550psi	550psi
	Lo	340psi	340psi	340psi	340psi
Indoor Fan Motor Load		0.7A	0.9A	0.4A	0.5A
Outdoor Fan Motor Load		0.8A	0.8A	0.9A	0.76A
Compressor Locked-Rotor Current		40.0A	47.0A	32.6A	34.8A
Minimum Circuit Ampacity		13.6A	17.2A	12.7A	16.5A
Sq ft Coverage		Up to 350	350-500	500-650	650-800
Control		Wireless Remote Control			
Max. Fuse		15.0A	20.0A	15.0A	20.0A
Indoor Unit	Dimension (W*H*D)	31"X11"X9"	36"X12"X9"	43"X13"X10"	49"X12"X10"
	Packing (W*H*D)	35"X15"X12"	40"X15"X12"	47"X18"X13"	54"X17"X13"
	Weight (Net/Gross)	16.5/19.8LB	28.6/33LB	33/46.2LB	39.6/55LB
Outdoor Unit	Dimension (W*H*D)	33"X21"X10"	33"X23"X10"	35"X27"X12"	38"X33"X12"
	Packing (W*H*D)	36"X23"X13"	36"X26"X14"	39"X30"X16"	42"X37"X16"
	Weight (Net/Gross)	70.4/77 lbs	83.6/90.2 lbs	116.6/125.4 lbs	143/151.8 lbs

- Features:**
1. Auto / Cool / Heat / Dry / Fan operation. Convenient wireless remote control.
 2. Night light feature.
 3. Airflow direction control.
 4. LED digital display.
 5. No duct work.
 6. Timer setting function in 24 hours.



Note: Specifications and performance data listed herein are subject to change without notice.